



SAFETY DATA SHEET (EUROPEAN)

SDS NUMBER: 600E Revision 30
DATE OF ISSUE: 11 December 1998

ACCORDING TO:(EC) No 1907/2006 and (EC) No1272/2008
DATE OF LAST REVISION 18th August 2015

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

IDENTIFICATION OF THE SUBSTANCE

TRADE NAMES: **ISOFRAX**

The above-mentioned product contains Alkaline-earth silicate wools (AES wools)
Index Number: 650-016-00-2 Annex VI
CAS number: 436083-99-7
Registration number: 01-2119457644-32-0001 and 01-2119457644-32-0002

USE OF THE PRODUCT

Application as thermal insulation, heat shields, heat containment, gaskets and expansion joints in industrial furnaces, ovens, kilns, boilers and other process equipment and in the aerospace, automotive and appliance industries, and as passive fire protection systems and firestops. (Please refer to specific technical data sheet for more information).

IDENTIFICATION OF THE MANUFACTURER/SUPPLIER

France

Unifrax France
17 Rue Antoine Durafour
42420 Lorette
France
Tel.: +33 (0) 4 7773 7000
Fax.:+33 (0) 4 7773 3991

UK

Unifrax Limited
Mill Lane, Rainford
St Helens, Merseyside
WA11 8LP
Tel: + 44 (0) 1744 88 7600
Fax: + 44 (0) 1744 88 9916

Germany

Unifrax GmbH
Kleinreinsdorf 62
07989 Teichwolframsdorf
Tel: + 49 (0) 366 24 40020
Fax: + 49 (0) 366 24 40099

Czech Republic

Unifrax s.r.o.,
Novosedicka 125
417 03 Dubi 3,
Czech Republic
Tel: + 42 (0) 417 800 356
Fax: + 42 (0) 417 539 838



SPAIN
Unifrax Spain
Cristobal Bordiu 20
Madrid 28003
Spain
Tel: + 34 91 395 2279
Fax: + 34 91 395 2124

ITALY
Unifrax Italia Srl
Via Volonterio 19
Saronno (Va) 21047
Italy
Tel: + 39 02 967 01 808
Fax: + 39 02 962 5721

Occupational Hygiene and CARE: Tel: + 44 (0) 1744 887603. Fax: + 44 (0) 1744 886173

E Mail : reachsds@unifrax.com

2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE/MIXTURE

The substance is exonerated from classification in accordance with nota Q.

Fibres contained in this product are therefore free of any classification and do not require labelling under CLP regulation.

ACCORDING TO REGULATION (EC) No 1272/2008 AMENDING AND REPEALING DIRECTIVES 67/548/EEC AND 1999/45/EC, AND AMENDING REGULATION (EC) No 1907/2006.

Under 1.1.3.1. (Nota Q) of Annex VI of regulation (EC) 1272/2008 the classification as a carcinogen 2 needs not apply on the basis of short term bio persistence test by intratracheal installation showing a half life of less than 40 days for fibres longer than 20 µm.

LABELLING ELEMENTS

Fibres contained in this product are free of any classification and do not require labelling under CLP regulation

OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure. These effects are usually temporary.

3. COMPOSITION / INFORMATION OF INGREDIENTS

COMPONENT	CAS NUMBER	Index Number
AES wool (synthetic fibres, alk. earth silicate)	436083-99-7*	650-016-00-2

AES Registration number: 01-2119457644-32-0001 and 01-2119457644-32-0002



ISOFRAX is an alkaline earth silicate (AES)* containing silica (SiO₂) (70-80wt%), magnesia (18- 27wt%).

* CAS definition: Alkaline earth silicate (AES) consisting of silica (50-82 wt%), calcia and magnesia (18-43 wt%), alumina, titania and zirconia (less than 6 wt%), and trace oxides.

None of the components are radioactive under the terms of European Directive Euratom 96/29.

DESCRIPTION

ISOFRAX products are available in the form of: bulks, blankets, papers, felts, boards, shapes, modules, cements, coatings, mixes and mastics. **According to product form, other ingredients may be present (see appended table).**

4. FIRST AID MEASURES

SKIN

In case of skin irritation rinse affected areas with water and wash gently. Do not rub or scratch exposed skin.

EYES

In case of eye contact flush abundantly with water; have eye bath available. Do not rub eyes.

NOSE AND THROAT:

If these become irritated move to a dust free area, drink water and blow nose.

If symptoms persist, seek medical advice.

5. FIRE-FIGHTING MEASURES

Non combustible products.

Packaging and surrounding materials may be combustible.

Use extinguishing agent suitable for surrounding combustible materials.

6. ACCIDENTAL RELEASE MEASURES

Where abnormally high dust concentrations occur, provide the workers with appropriate protective equipment as detailed in section 8.

Restore the situation to normal as quickly as possible.

Prevent further dust dispersion for example by damping the materials.

Pick up large pieces and use a vacuum cleaner fitted with high efficiency filter (HEPA)

If brushing is used, ensure that the area is wetted down first.

Do not use compressed air for clean-up.

Do not allow to be wind blown.

Do not flush spillage to drain..

For wastes disposal refer to section 13



7. HANDLING AND STORAGE

HANDLING / TECHNIQUES TO REDUCE DUST EMISSIONS DURING HANDLING

HANDLING

Handling can be a source of dust emission.

The Process or processes should be designed to limit the amount of handling. Whenever possible, handling should be carried out under controlled conditions (i.e., use dust exhaust system).

Regular good housekeeping will minimise secondary dust dispersal.

STORAGE

Store in original packaging in dry area whilst awaiting use

Always use sealed and visibly labelled containers.

Avoid damaging containers.

Reduce dust emission during unpacking.

Emptied containers, which may contain debris, should be cleaned before disposal or recycling.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

HYGIENE STANDARDS AND EXPOSURE LIMITS

Industrial hygiene standards and occupational exposure limits vary between countries and local jurisdictions. Check which exposure levels apply to your facility, and comply with local regulations. If no regulatory dust or other standards apply, a qualified industrial hygienist can assist with a specific workplace evaluation including recommendations for respiratory protection. Examples of exposure limits applying (in January 2010) to mineral wools in different countries are given below:

COUNTRY	EXPOSURE LIMIT*	SOURCE
Germany	3 mg/m ³	TRGS 900
France	1.0 f/ml	Circulaire DRT No 95-4 du 12.01.95
U.K.	2.0 f/ml and 5 mg/m ³	HSE - EH40 – Workplace Exposure Limit

**Time weighted average concentrations of airborne respirable fibres measured over 8 hours by the conventional membrane filter method or the total inhalable dust using standard gravimetric techniques.*

ENGINEERING CONTROLS

Review your application(s) in order to identify potential sources of dust exposure.

Local exhaust ventilation, which collects dust at source, can be used. For example down draft tables, emission controlling tools and material handling equipment.

Keep the workplace clean. Use a vacuum cleaner fitted with an HEPA filter; avoid brushing and using compressed air.



PERSONAL PROTECTIVE EQUIPMENTS

SKIN PROTECTION

Wear gloves and work clothes, which are loose fitting at the neck and wrists. Soiled clothes should be cleaned to remove excess fibres before being taken off (e.g. use vacuum cleaner, not compressed air)..

EYE PROTECTION

As necessary wear goggles or safety glasses with side shields

RESPIRATORY PROTECTION

For dust concentrations below the exposure limit value, RPE is not required but FFP2 respirators may be used on a voluntary basis.

For short term operations where excursions are less than ten times the limit value use FFP2 respirators.

In case of higher concentrations or where the concentration is not known, please seek advice from your company and/or your supplier.

INFORMATION AND TRAINING OF WORKERS

Workers should be trained on good working practices and informed on applicable local regulations.

ENVIRONMENTAL EXPOSURE CONTROLS

Refer to local, national or European applicable environmental permitted standards for release to air, water and soil.

For waste, refer to section13

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	White fibre	PARTITION COEFFICIENT	Not applicable
BOILING POINT	Not applicable	ODOUR	None
FLASH POINT	Not applicable	FIBRE MELTING POINT	1500-1550° C
AUTOFLAMMABILITY	None	FLAMMABILITY	Not applicable
OXIDISING PROPERTIES	None	EXPLOSIVE PROPERTIES	None
RELATIVE DENSITY	2.6	VAPOUR PRESSURE	Not applicable
SOLUBILITY	Less than 1 mg/l	pH	Not applicable



**LENGTH WEIGHTED GEOMETRIC MEAN
DIAMETER OF FIBRES CONTAINED IN THE
PRODUCT**

1.9 - 6 µm

10. STABILITY AND REACTIVITY

CONDITIONS AND MATERIALS TO AVOID

None

DECOMPOSITION PRODUCTS

Upon heating above 900°C for sustained periods, this amorphous material begins to transform to mixtures of crystalline phases. For further information please refer to Section 16.

11. TOXICOLOGICAL INFORMATION

Irritant Properties

When tested using approved methods (Directive 67/548/EC, Annex V, Method B4), fibres contained in this material give negative results. All man made mineral fibres, like some natural fibres, can produce a mild irritation resulting in itching or rarely, in some sensitive individuals, in slight reddening. Unlike other irritant reactions this is not the result of allergy or chemical skin damage but is caused by a temporary mechanical effect.

Other Animal Studies

These materials have been designed to allow rapid clearance from tissue. And this low biopersistence has been confirmed in many studies using EU protocol ECB/TM/27(rev 7) and the German method specified in TRGS 905 (1999). When inhaled, even at very high doses, they do not accumulate to any level capable of producing a serious adverse biological effect. In lifetime chronic studies there was no exposure-related effect more than would be seen with any "inert" dust. Subchronic studies at the highest doses achievable produced, at worst, a transient mild inflammatory response. Fibres with the same ability to persist in tissue do not produce tumours when injected into the peritoneal cavity of rats.

12. ECOLOGICAL INFORMATION

These products are inert materials, which remain stable overtime.
No adverse effects of this material on the environment are anticipated.

13. DISPOSAL CONSIDERATIONS

Waste from these products are classed as non hazardous and may generally be disposed of at landfill, which has been licensed for this purpose. Please refer to the European list (Decision no 2000/532/CE as modified) to identify your appropriate waste number, and insure national and or regional regulation are complied with. Taking into account any possible contamination during use, expert guidance should be sought.

Unless wetted, such a waste is normally dusty and so should be properly sealed in clearly labelled containers for disposal. At some authorised disposal sites, dusty waste may be treated differently in order to ensure they are dealt with promptly to avoid them being wind blown. Check for national and/or regional regulations, which may apply



14. TRANSPORT INFORMATION

Not classified as dangerous goods under relevant international transport regulations (ADR, RID, IATA, IMDG AND Refer Section 16 "Definitions").

Ensure that dust is not wind blown during transportation.

15. REGULATORY INFORMATION

1. FIBRE TYPE DEFINITION UNDER DIRECTIVE 67/548/EEC

According to Directive 67/548/EEC the fibre contained in this product is a mineral wool belonging to the group of "man-made vitreous (silicate) fibres with random orientation with alkaline earth oxide ($\text{Na}_2\text{O}+\text{K}_2\text{O}+\text{CaO}+\text{MgO}+\text{BaO}$) content greater to 18% by weight".

Under criteria listed in nota Q of Directive 67/548/EEC, fibres contained in the products listed in the title are exonerated from carcinogen classification because of low pulmonary bio persistence measured by the methods specified in European Union and German regulations (EU protocol ECBT/TM/27(rev 7)).

31st Adaptation to Technical Progress of Directive 67/548/EEC of 15 January 2009 has removed skin irritancy classification for man-made vitreous (silicate) wools.

2. FIBRE TYPE DEFINITION ACCORDING TO REGULATION (EC) No 1272/2008 AMENDING AND REPEALING DIRECTIVES 67/548/EEC AND 1999/45/EC, AND AMENDING REGULATION (EC) No 1907/2006.

This regulation aims at incorporating the GHS criteria into the EU Community law.

Under 1.1.3.1. (Nota Q) of Annex VI of regulation (EC) 1272/2008 the classification as a carcinogen 2 needs not apply on the basis of short term bio persistence test by intratracheal installation showing a half life of less than 40 days for fibres longer than 20 μm .

1st Adaptation of Technical Progress of regulation (EC) N°1272/2008 of 10 August 2009 has removed skin irritancy classification for man-made vitreous (silicate) wools.

Fibres contained in this product are therefore free of any classification and do not require labelling under CLP regulation.

PROTECTION OF WORKERS

Shall be in accordance with several European Directives as amended and their implementations by the Member States:

- a) Council Directive 89/391/EEC dated 12 June 1989 "on the introduction of measures to encourage improvements in the safety and health of workers at work" (OJEC (Official Journal of the European Community) L 183 of 29 June 1989, p.1).
- b) Council Directive 98/24/EC dated 7 April 1998 "on the protection of workers from the risks related to chemical agents at work" (OJEC L 131 of 5 May 1998, p.11).

OTHER POSSIBLE REGULATIONS

Member States are in charge of implementing European Directives into their own national regulation within a period of time normally given in the Directive. Member States may impose more stringent requirements. Please always refer to any national regulation.

This applies for sales in the European Union



16. OTHER INFORMATION

USEFUL REFERENCES (the directives which are cited must be considered in their amended version)

- Council Directive 89/391/EEC dated 12 June 1989 “on the introduction of measures to encourage improvements in the safety and health of workers at work” (OJEC L 183 of 29 June 1989, p.1).
- Regulation (EC) No 1907/2006 dated 18th December 2006 on Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 dated 20th January 2009 on classification, labeling and packaging of substances and mixtures (OJ L 353)
- Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress for the 23rd time Council Directive 67/548/EEC (OJEC of 13 December 1997, L 343).
- Council Directive 98/24/EC of 7 April 1998 “on the protection of the health and safety of workers from the risks related to chemical agents at work” (OJEC L 131 of 5 May 1998, p11).

DEFINITIONS

ADR	Transport by road, council directive 94/55/EC
IMDG	Regulations relating to transport by sea
RID	Transport by rail, Council Directive 96/49/EC
ICAO/IATA	Regulations relating to transport by air
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

PRECAUTIONARY MEASURES TO BE TAKEN AFTER SERVICE UPON REMOVAL

In almost all applications high temperature insulating wools products (HTIW) are used as an insulating material helping to maintain the temperature at 900°C or more in a closed space. As produced, *Isotrax* fibres are vitreous (glassy) materials which, upon continued exposure to elevated temperatures (above 900°C) might de-vitrify. The occurrence and extent of crystalline phase formation is dependent on the duration and temperature of exposure, fibre chemistry and/or the presence of fluxing agents. As only a thin layer of the insulation hot face side is exposed to high temperature, respirable dust generated during removal operations does not contain detectable levels of crystalline silica (CS)

In applications where the material is heat soaked, duration of heat exposure is normally short and a significant devitrification allowing CS to build up does not occur. This is the case for waste mould casting for instance.

Toxicological evaluation of the effect of the presence of CS in artificially heated HTIW material has not shown any increased toxicity in vitro and in vivo. The results from different combinations of factors like increased brittleness of fibres, or microcrystals embedded in the glass structure of the fibre and therefore not biologically available may explain the lack of toxicological effects.

IARC evaluation as provided in Monograph 68 is not relevant as CS is not biologically available in after service HTIW.

High concentrations of fibres and other dusts may be generated when after-service products are mechanically disturbed during operations such as wrecking. Therefore ECFIA recommends:

- control measures are taken to reduce dust emissions; and
- all personnel directly involved wear an appropriate respirator to minimise exposure and comply with local regulatory limits.

CARE PROGRAMME



ECFIA, Representing the High Temperature Insulation wools Industry, has undertaken an extensive industrial hygiene programme for High Temperature Insulation Wool (HTIW).

The objectives are twofold:

- to monitor workplace dust concentrations at both manufacturers' and customers' premises,
- to document manufacturing and use of HTIW products from an industrial hygiene perspective in order to establish appropriate recommendations to reduce exposures.

If you wish to participate in the CARE programme, contact ECFIA or your supplier.

NOTE

The directives and subsequent regulations detailed in this Material Safety Data Sheet are only applicable to the European Union (EU) Countries and not to countries outside of the EU.

WEBSITES:

For more information connect to:

European Industry Association Representing HTIW (ECFIA): 3, Rue du Colonel Moll, 75017 Paris
Tel. +33 (0) 6 31 48 74 26

the ECFIA's website: (<http://www.ecfia.eu>)

NOTICE:

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Safety Data Sheet. Employers may use this SDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this SDS. Therefore, given the summary nature of this document, Unifrax I LLC does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.



Other Ingredients in Isofrax Products

PRODUCTS	Significant Ingredients (% by weight)	H Statement	P Statements
Non-lubricated bulk	None	None	None
Lubricated bulk	Organic lubricant (<1%)	None assigned	None assigned
High Index Fibres	None	None	None
Blankets	None	None	None
Papers and Felts Flexilite-MC Paper Flexilite-MC Felt	Acrylic latex (< 12%)	None Assigned	None Assigned
Papers and Felts Isofrax 880 paper	Acrylic latex (< 12%) Inorganic Binder (<10%)	None Assigned None Assigned	None Assigned None Assigned
Boards and Shapes Isofrax Board 120LD, Boiler parts 110CM	Amorphous Silica (5-40%)	None	None
Boards and Shapes Millboard 120KB	Amorphous Silica (5-40%) Clay (<75%) Cellulose (<10%)	None None None	None None None
Boards and Shapes Isofrax Board 120ZK	Amorphous Silica (5-40%) Clay (<10%) Cellulose (<5%)	None None None	None None None
Boards and Shapes Isofrax fire products	Amorphous Silica (5-20%) Inorganic pigments (<5%)	None None	None None
Boards and Shapes Boiler Parts 120BA	Amorphous Silica (5-40%) Clay (<10%)	None None	None None
Boards and Shapes Silin HT	Amorphous Silica (10-30%) Clay (10% -50%)	None None	None None
Boards and Shapes Isofrax Riform 120, 120HD, 120s	Amorphous Silica (5-40%)	None	None
Specialty products Isofrax Flexiform 120	*Organic binders (<15%) Amorphous silica (<5%)	None None	None None
Prismo - Block	None	None	None



Bonded Modules	None	None	None
Textiles	None	None	None
Specialty products Moist pak HD	Amorphous silica 5-20% Alumina 5-20%	None None	None None
Mixes / Mastics Isofrax castable KUB	Calcium Aluminate (<40%)	None	None
Mixes/ Mastic Isofrax castable 110	Calcium Aluminate (,20%) Calcined clay (50-65%)	None	None
Mastic Isofrax Pumpable 120 Isofrax mouldable 120	Amorphous silica (5-50%)	None	None